Encon®
SAFETY PRODUCTS
1-800-283-6266
phone: (713) 466-1449
email: customerservice@enconsafety.com

PEDESTAL MOUNT EYEWASH WITH YELLO-BOWL®

PART NUMBER: 01030302

SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 3.2 gpm (12. 1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Eyewash shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½" chrome plated (CP) single motion activation stay open ball valve with CP ball. Eyewash shall include S/S actuator with actuation graphic, 7" X 11" (17.8cm X 27.9cm) sign, ½" (CP) brass piping and schedule 80 hot dip galvanized pedestal mount/drain for free-standing installation. Unit must be supplied with self-adjusting 3.2 gpm (12.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads with hinged flip covers to be manufactured of UV resistant ABS plastic mounted in a high visibility ABS plastic Yello-Bowl®. Hinged flip covers are provided to inhibit dust and/or contamination when not in use. Eyewash units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable.

Encon Safety Products Model 01030302 includes pedestal mount eyewash with Yello-Bowl®

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

PIPING: ½" Chrome plated brass supply piping and schedule 80 hot dipped galvanized pedestal mount/drain.
VALVES: ½" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic.
HEAD: ABS plastic dual stream heads with hinged flip covers.
BOWL: High visibility ABS plastic Yello-Bowl®.
REGULATOR: Self-adjusting 3.2 gpm (12.1 lpm) regulator assures a constant and even dual stream flow pattern under varying hydraulic conditions.
SUPPLY: ½" NPT
WASTE: 1 ¼" NPT
WEIGHT: 25 lbs (11.34 kgs)



© 2023 Encon Safety Products, Inc.