Encon®
SAFETY PRODUCTS
1-800-283-6266
phone: (713) 466-1449
email: customerservice@enconsafety.com

WHEELCHAIR ACCESSIBLE COMBO SHOWER & FACEWASH W/ YELLO-BOWL®

PART NUMBER: 01050275

SPECIFICATION:

Third party certified to ANSI Z358.1, the wheelchair accessible combination shower and facewash unit shall deliver 30 gpm (113.6 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure from the shower head and 8.0 gpm (30.3 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure from the facewash. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Combination unit shall be supplied with chrome plated (CP) bronze single motion activation stay open ball valves with CP balls. Valve sizes: shower 1", eyewash ½". Unit shall include SS actuators with actuation graphics, schedule 80 hot dip galvanized steel piping and 1¼" supply/waste connection with flanged floor mounting plate for free-standing installation. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator. Facewash heads to be supplied with self-adjusting 8.0 gpm (30.3 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of UV resistant high visibility yellow ABS plastic. Shower head must deliver a minimum of 20" (50.8 cm) diameter pattern to the target area 60" (152.4 cm) above standing level. Eye/Facewash heads with float off covers to be manufactured of UV resistant ABS plastic mounted in a high visibility ABS Yello-Bowl®. Eye/facewash float off covers are secured with stainless steel bead chains and provided to inhibit dust and/or contamination when not in use. Combination units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable.

Encon Safety Products Model 01050275 includes Wheelchair accessible shower, facewash combination unit.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.



MATERIALS OF CONSTRUCTION:

PIPING: Schedule 80 hot dip galvanized steel.
VALVES: Chrome plated bronze stay open ball valves with CP balls, stainless steel valve stems, stainless steel push plate with actuation graphic (eyewash) and stainless steel chain with actuation graphic.
SHOWER HEAD: Yellow ABS plastic shower head.
EYEWASH HEAD: ABS plastic dual stream heads with ABS plastic float off covers secured with stainless steel bead chains.
BOWL: High visibility ABS plastic Yello-Bowl®.
REGULATOR: Self-adjusting 30 gpm (113.6 lpm) shower and 8.0 gpm (30.3 lpm) eyewash regulators.
SUPPLY: 1 ¼" NPT
WASTE: 1 ¼" NPT
WEIGHT: 63 lbs (28.57 kgs)

© 2023 Encon Safety Products, Inc.