



1-800-283-6266

phone: (713) 466-1449

email: customerservice@enconsafety.com

PEDESTAL EYEWASH WITH SST BOWL AND SST BOWL COVER

Model Number: 01045002SBC

SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 2.4 gpm (9.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½" brass chrome plated (BCP) single motion activation stay open ball valve with CP ball. Eyewash shall include S/S actuator with actuation graphic, 7" X 11" (17.8cm X 27.9cm) sign, schedule 80 hot dip galvanized pedestal mount/waste for freestanding installation. Unit must be supplied with self-adjusting 2.4 gpm (9.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) water pressure conditions. Eyewash heads with integral hinged covers to be manufactured of solvent resistant acetal mounted on a chrome plate brass wye in a type 304 SS bowl. Eyewash covers are provided to inhibit dust and/or contamination when not in use. Eyewash units with deteriorating screens/filters are not acceptable. Eyewash shall be Encon Safety Products Model **01045002SBC**.

***Note:** Where hazardous materials are used that are injurious to the skin, a proper eyewash or eye/facewash installation with the shower is recommended.

MATERIALS OF CONSTRUCTION:

PIPING: Hot dip galvanized steel schedule 80.

VALVE: ½" chrome plated bronze stay open ball valve with chrome plated ball, stainless-steel valve stem and stainless-steel push plate with actuation graphic.

EYEWASH HEAD: Acetal dual stream heads with integral hinged covers and chrome plated brass wye assembly.

BOWL: Type 304 stainless steel.

BOWL COVER: Type 304 stainless steel

REGULATOR: Self-adjusting (2) 1.2 gpm (4.5 lpm) regulators.

SUPPLY: ½" NPT

WASTE: 1¼" NPT

WEIGHT: 25 lbs (11.34 kgs)

