



1-800-283-6266

phone: (713) 466-1449 | fax: (713) 466-1703
email: customerservice@enconsafety.com

FW, BCP PIPE, SS BOWL & COVER, WALL BRACKET, BCP WYE Model Number: 01045501SBC

SPECIFICATION:

Third party certified to ANSI Z358.1, the face/eyewash shall deliver 8.0 gpm (30.3 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½" brass chrome plated (BCP) single motion activation stay open ball valve with CP ball. Face/eyewash shall include S/S actuator with actuation graphic, 304 SST wall bracket, brass chrome plate mount/waste for wall mounting installation. Unit must be supplied with self-adjusting 4.0 gpm (15.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) water pressure conditions. Face/eyewash heads to be manufactured of ABS plastic mounted on a brass chrome plated wye in a type 304 SS bowl and 304 SS bowl cover. Face/eyewash units with deteriorating screens/filters are not acceptable. Face/eyewash shall be Encon Safety Products Model 01045501SBC.

***Note:** Where hazardous materials are used that are injurious to the skin, a proper eyewash or eye/facewash installation with the shower is recommended.

MATERIALS OF CONSTRUCTION:

MOUNTING: 304 stainless steel 14 ga. bracket

VALVE: ½" chrome plated bronze stay open ball valve with chrome plated ball, stainless-steel valve stem and stainless-steel push plate with actuation graphic.

EYEWASH HEAD: ABS plastic dual stream heads with brass chrome plated wye assembly.

BOWL: Type 304 stainless steel.

BOWL COVER: Type 304 stainless steel

REGULATOR: Self-adjusting (2) 4.0 gpm (15.1 lpm) regulators.

SUPPLY: ½" NPT

WASTE: 1¼" NPT

WEIGHT: 11 lbs (5 kgs)

