



EYEWASH
PART NUMBER: 01030101

SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 3.2 gpm (12.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Eyewash shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 1/2" chrome plated (CP) single motion activation stay open ball valve with CP ball. Eyewash shall include actuator with actuation graphic and 7" X 11" (17.8 cm X 27.9 cm) sign. Unit must be supplied with self-adjusting 3.2 gpm (12.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads with hinged flip covers to be manufactured of UV resistant ABS plastic. Hinged flip covers are provided to inhibit dust and/or contamination when not in use. Eyewash units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable. **Encon Safety Products Model 01030101** includes eyewash

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

PIPING: 1/2" Chrome plated brass.

VALVES: 1/2" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless-steel push plate with actuation graphic.

HEAD: ABS plastic dual stream heads with hinged flip covers.

REGULATOR: Self-adjusting 3.2 gpm (12.1 lpm).

SUPPLY: 1/2" NPT

WEIGHT: 4 lbs (1.81 kgs)

