

**Encon**<sup>®</sup>  
SAFETY PRODUCTS

1-800-283-6266

Phone: (713) 466-1449 Fax: (713) 466-1703  
E-Mail: [customerservice@enconsafety.com](mailto:customerservice@enconsafety.com)



# COUNTER TOP EYEWASH/ HOSE STATION

PART NUMBER: 01040114

**SPECIFICATION:**

Third party certified to ANSI-Z358.1, the eyewash shall deliver 2.4 gpm (9.1 lpm) @ 45/70 psi (310.6/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 3/8" chrome plated (CP) single motion activation stay open ball valve with CP ball. Valve provides quick operation with a positive stop. Additionally, unit shall include S/S actuator with actuation graphic, 7" x 11" (17.8cm X 27.9cm) sign and countertop mounted eyewash swivel fitting. Swivel fitting allows unit to be used as a fixed eyewash or is removable for localized drench use. Eyewash shall be supplied with self-adjusting 2.4 gpm (9.1 lpm) regulator to assure a constant and even dual stream flow pattern under 40/70 psi (310.6/482.6 kPa) hydraulic conditions. Eyewash heads with integral hinged covers to be manufactured of solvent resistant acetal mounted on chrome plated brass wye. Eyewash covers are provided to inhibit dust and/or contamination when not in use. Eyewash units with deteriorating screens/filters are not acceptable. Eyewash/drench hose unit shall be Encon Safety Products Model 01040114.

**MATERIALS OF CONSTRUCTION:**

- PIPING:** Chrome plated brass.
- VALVE:** 3/8" Chrome plated bronze ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic.
- HEAD:** Acetal dual stream heads with integral hinged covers and chrome plated brass wye assembly.
- DRENCH HOSE UNIT:** 6' (152.40cm) nylon coiled hose with swivel fitting.
- REGULATOR:** Self-adjusting (2) 1.2 gpm (4.5 lpm) regulators.
- SUPPLY:** 3/8" NPT
- WEIGHT:** 10 lbs (4.54 kgs)
- PRESSURE:** Requires 45 psi (310.6 kPa) flowing pressure.

