

Encon[®]
SAFETY PRODUCTS
1-800-283-6266
 phone: (713) 466-1449
 email: customerservice@enconsafety.com

EYEWASH W/STAINLESS STEEL BOWL, WALL MOUNT & PLASTIC BOWL COVER
PART NUMBER:01045001PBC

SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 2.4 gpm (9.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½” chrome plated (CP) single motion activation stay open ball valve with CP ball. Eyewash shall include stainless steel (SS) actuator with actuation graphic, 7” X 11” (17.8cm X 27.9cm) sign and SS wall mounting bracket. Unit must be supplied with self-adjusting 2.4 gpm (9.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads manufactured of solvent resistant acetal mounted on chrome plated brass wye in a type 304 SS bowl. Eyewash includes a highly visible ABS cover to inhibit dust and/or particulate accumulation on the eyewash heads when not in use. The cover shall open immediately on actuation of the eye/face wash valve and will be able to be opened or closed manually. Eyewash units with deteriorating screens/filters are not acceptable. **Encon Safety Products Model 01045001PBC** includes eyewash with stainless steel bowl, wall mount and plastic bowl cover.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

- PIPING:** ½” Chrome plated brass.
- VALVES:** ½” Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic.
- HEAD:** Chrome plated brass wye with acetal heads.
- BOWL:** Type 304 stainless steel bowl with S/S wall mount bracket
- COVER:** Hinged cover made from high visibility yellow ABS plastic.
- REGULATOR:** Self-adjusting (2) 1.2 gpm (4.5 lpm) regulators.
- SUPPLY:** ½” NPT
- WASTE:** 1¼” NPT (1¼” tailpiece with p-trap optional).
- WEIGHT:** 9 lbs (4.08 kgs)

