

**Encon<sup>®</sup>**  
**SAFETY PRODUCTS**  
**1-800-283-6266**  
 phone: (713) 466-1449  
 email: customerservice@enconsafety.com

# EYEWASH W/ STAINLESS STEEL BOWL, 2.5 GPM SS EYEWASH HEADS AND BRACKET

## PART NUMBER: 01045015

**SPECIFICATION:**

Third party certified to ANSI Z358.1, the eyewash shall deliver 2.5 gpm (9.5 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 1/2" chrome plated (CP) single motion activation stay open ball valve with CP ball. Eyewash shall include stainless steel (SS) actuator with actuation graphic, 7" X 11" (17.8cm X 27.9cm) sign and SS wall mounting bracket. Unit must be supplied with self-adjusting 2.5 gpm (9.5 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads with integral hinged covers to be manufactured of stainless steel in a type 304 SS bowl. Eyewash covers are provided to inhibit dust and/or contamination when not in use. Eyewash units with deteriorating screens/filters are not acceptable.

**\*Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

**MATERIALS OF CONSTRUCTION:**

- PIPING:** 1/2" SS piping.
- VALVES:** 1/2" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless-steel push plate with actuation graphic.
- HEAD:** SS heads with hinged covers.
- BOWL:** Type 304 stainless steel bowl with S/S wall mount bracket
- REGULATOR:** Self-adjusting regulator to flow at 2.5 gpm (9.5 lpm)
- SUPPLY:** 1/2" NPT
- WASTE:** 1/4" NPT (1/4" tailpiece and p-trap optional).
- WEIGHT:** 9 lbs (4.08 kgs)

