

Encon[®]
SAFETY PRODUCTS
1-800-283-6266
 phone: (713) 466-1449
 email: customerservice@enconsafety.com

EYE/FACEWASH W/ STAINLESS STEEL BOWL AND WALL MOUNT

PART NUMBER:01045501

SPECIFICATION:

Third party certified to ANSI Z358.1, the eye/facewash shall deliver 8.0 gpm (30.3 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer as required by ANSI Z358.1. Unit shall be supplied with 1/2" chrome plated (CP) single motion activation stay open ball valve with CP ball. Eye/Facewash shall include stainless steel (SS) actuator with actuation graphic, 7" X 11" (17.8 cm X 27.9 cm) sign and wall mounting bracket. Unit must be supplied with 8.0 gpm (30.3 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eye/Facewash heads with float off covers to be manufactured of UV resistant ABS plastic mounted on a chrome plated brass wye in type 304 SS bowl. Float off covers are secured with stainless steel bead chains and provided to inhibit dust and/or contamination when not in use. Eye/Facewash units with deteriorating screens/filters are not acceptable. **Encon Safety Products Model 01045501** includes eye/facewash with stainless steel bowl and wall mount.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

- PIPING:** 1/2" Chrome plated brass.
- VALVES:** 1/2" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic. Strainer Tee Option: 1/2" BCP, 16 mesh. P-trap Option: 1/4" Satin BCP
- HEAD:** ABS plastic dual stream heads with ABS plastic float off covers secured with stainless steel bead chains and chrome plated brass wye assembly.
- BOWL:** Type 304 stainless steel bowl with SS wall bracket.
- REGULATOR:** Self-adjusting (2) 4.0 gpm (15.1 lpm) regulators.
- SUPPLY:** 1/2" NPT
- WASTE:** 1 1/4" NPT (p-trap optional).
- WEIGHT:** 9 lbs (4.08 kgs)

