

Encon[®]
SAFETY PRODUCTS
1-800-283-6266
 phone: (713) 466-1449
 email: customerservice@enconsafety.com

DRAIN PAN ASSEMBLY

PART NUMBER: 01052232

SPECIFICATION:

Drain pan assembly, 36" x 36" fiberglass, stainless steel and galvanized hardware. The drain pan is placed directly underneath the user's grate (in multi-level process areas). The shower is installed next to the customer grate on a solid surface level or appropriate support. The shower should be placed above the drain pan to appropriately collect the flushing fluid below the grate. The drain pan attaches underneath 1" structural open grates in multi-level process areas by 8 anchor clips positioned on the outer rim of the pan as pictured above. The shower/eyewash station would be installed on top of grate above the drain pan. The drain in the center of the pan is a PVC slip joint with 3" ID and 4" OD. Field pipe installation to the center drain is a maximum 2" schedule 80 slip-in type pipe insertion depth of 1 1/2".

Encon Safety Products Model 01052232 includes drain pan assembly

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

PAN: Fiberglass

HARDWARE: SST and Galvanized

DRAIN PAN CONNECTION: Drain fitting is a PVC slip joint (5.1 cm inside dims / 7.6 cm outside dims)

Drain pipe insertion depth: 1-1/2" (3.8 cm).

WEIGHT: 5 lbs (2.27 kgs)

