



# HORIZONTAL SHOWER w/ SS PIPING & SS STAY-OPEN BALL VALVE PART NUMBER: 01053004

## SPECIFICATION:

Third party certified to ANSI Z358.1, the shower shall deliver 30 gpm (113.6 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Shower shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 1 1/4" chrome plated (CP) bronze single motion activation stay open ball valve with CP ball, SS actuator with actuation graphic, schedule 80 hot dip galvanized steel piping and 1 1/4" supply connection. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator to assure a constant flow and pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of UV resistant high visibility yellow ABS plastic. Shower head must deliver a minimum of 20" (50.8 cm) diameter pattern to the target area 60" (152.4 cm) above standing level. Shower units that provide improper flow pattern not acceptable.

**Encon Safety Products Model 01053004** Includes Horizontal Shower Unit w S/S Piping, SS Stay-Open Ball valve.

## MATERIALS OF CONSTRUCTION:

**PIPING:** Schedule 80 hot dip galvanized piping.

**VALVES:** 1 1/4" chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless pull rod assembly with actuation graphic.

**SHOWER HEAD:** Yellow ABS plastic shower head. Option: Type 304 stainless steel shower head.

**REGULATOR:** Self-adjusting 30 gpm (113.6 lpm) regulator.

**SUPPLY:** 1 1/4" NPT

**WEIGHT:** 11 lbs (4.98 kgs)

**\*Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

