

Encon[®]
SAFETY PRODUCTS
1-800-283-6266
 phone: (713) 466-1449
 email: customerservice@enconsafety.com

**20 GPM ABS
 SHOWER HEAD
 PART NUMBER: 01054005**

SPECIFICATION:

Shower head shall provide a non-injurious stream of water when mounted 96”(243.84cm) to 82”(208.28cm) from standing level. Shower head shall be supplied with self-adjusting 20 gpm (75.7 lpm) regulator to assure a constant flow and pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of UV resistant high visibility yellow ABS plastic. Shower head shall deliver a minimum of 20” (50.8 cm) diameter pattern to the target area 60” (152.4 cm) above standing level. Shower units that provide improper flow pattern are not acceptable. Shower unit shall be **Encon Safety Products Model 01054005** includes 20 GPM shower head

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

SHOWERHEAD: Yellow ABS plastic shower head.

REGULATOR: Self-adjusting 20 gpm (75.7 lpm) regulator.

SUPPLY: 1” NPT

WEIGHT: 1 lbs (0.45 kgs)

