



1-800-283-6266

Phone: (713) 466-1449 Fax: (713) 466-1703

E-Mail: customerservice@enconsafety.com

DRENCH HOSE w/MOUNTING BRACKET AND STAY OPEN BALL VALVE PART NUMBER: 01090007

SPECIFICATION:

Unit shall provide a non-injurious stream of water for 15 minutes or longer as required by ANSI Z358.1*. Unit shall be supplied with ½" chrome plated (CP) bronze single motion activation stay open ball valve with CP ball. Unit shall include SS actuator with actuation graphic, 7" x 11" (17.8cm X 27.9cm) sign, 6 foot (182.9cm) synthetic rubber hose, wall mounting bracket and ½" NPT connection. Drench hose head assembly with float off cover to be manufactured of UV resistant ABS plastic. Float off cover is secured with stainless steel bead chain and provided to inhibit dust and/or contamination when not in use. Drench hose units with deteriorating screens/filters are not acceptable. Drench hose unit shall be Encon Safety Products Model 01090007.

***Note:** Single stream drench hose units do not satisfy ANSI Z358.1 dual stream eyewash requirements and should only be used in support of primary eyewash equipment.

MATERIALS OF CONSTRUCTION:

VALVE: ½" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic.

DRENCH HOSE HEAD: Yellow ABS plastic single stream head with ABS plastic float off cover secured with stainless steel bead chain.

HOSE: 6' (182.9cm) synthetic rubber hose.

BRACKET: Vinyl coated wall mount bracket secures head when not in use.

SUPPLY: ½" NPT

WEIGHT: 5 lbs (2.26 kgs)

