

Encon[®]
SAFETY PRODUCTS
1-800-283-6266
 phone: (713) 466-1449
 email: customerservice@enconsafety.com

**SELF CONTAINED
 GRAVITY FED EYEWASH
 PART NUMBER: 01104050**

SPECIFICATION:

Third party certified to ANSI Z358.1, the self-contained gravity fed eyewash shall deliver a non-injurious dual stream of water at a minimum volume of 0.4 gpm (1.5 lpm) for a full 15 minutes or longer. The eyewash heads are integral in an enclosed tray that provides protection against airborne contaminants when the eyewash is in a ready, non-activated state. When activated the pull down tray goes to a fixed, stay open position that allows full user access to the dual streams of fluid and channels spent fluids to a discharge port where an optional drain tray can be provided. Unit shall supply a minimum six gallons of useable flushing fluid stored in a yellow polyethylene tank that is noncorrosive by potable water. The highly visible eyewash incorporates front graphics to indicate activation method, maintenance and operational information. Two sturdy handles on the sides are included to assist when relocation of the unit is required.

Encon Safety Products Model 01104050 includes self-contained gravity fed eyewash.

Encon Safety Products Model 01104055 includes self-contained gravity fed eyewash with transport cart and fluid collection receptacle.

Encon Safety Products Model 01110729 includes self-contained gravity fed eyewash with Additional Drain Tray Assembly.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

TANK: High visibility yellow polyethylene.

VALVE: Pinch hose valve.

HEAD: ABS plastic dual stream heads.

WATER TREATMENT ADDITIVE: 1 Bottle of Hydrosep[®] shipped with each unit. Treats 5 to 20 gallons (18.9 l to 75.7 l) up to 90 days.

WEIGHT: 15.2 lbs (6.9 kgs)

