



HELIOS[®]
SELF-CONTAINED
GRAVITY FED EYEWASH
PART NUMBER: HE100

SPECIFICATION:

Third party certified to ANSI Z358.1, the self-contained gravity fed eyewash shall deliver a non-injurious dual stream of water at a minimum volume of 0.4 gpm (1.5 lpm) for a full 15 minutes or longer. The eyewash heads are integral in an enclosed tray that provides protection against airborne contaminants when the eyewash is in a ready, non-activated state. When activated the pull down tray goes to a fixed, stay open position that allows full user access to the dual streams of fluid and channels spent fluids to a discharge port where an optional drain tray can be provided. Unit shall store maximum 10 gallons of useable flushing fluid stored in a yellow polyethylene tank that is noncorrosive by the flushing fluid. The highly visible, yellow ABS eyewash incorporates front graphics to indicate activation method, maintenance and operational information.

Encon Safety Products Model HE100 includes self-contained gravity fed eyewash unit.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

TANK: 10-gallon high visibility yellow polyethylene.

VALVE: Internal, rotating ABS actuating valve integral to the eye wash tray.

HEAD: ABS plastic dual stream heads installed directly into the eyewash tray.

WATER TREATMENT ADDITIVE: Single bottle of Hydrossep[®] potable water preservative shipped with each unit. Bottle treats fluids for up to 120 days (not to exceed 180 days).

WEIGHT: 15 lbs (6.8 kgs) shipping weight. 87 lbs (39.5 kgs) full-use weight (with water and additive).

