

**Encon<sup>®</sup>**  
**SAFETY PRODUCTS**  
**1-800-283-6266**  
**phone: (713) 466-1449**  
**email: customerservice@enconsafety.com**

**WHEELCHAIR ACCESSIBLE  
COMBINATION SHOWER/FACEWASH  
w/SS BOWL  
PART NUMBER: 01050394SS**

**SPECIFICATIONS:**

Wheelchair accessible combination shower and eye/facewash unit shall deliver 30 gpm (113.6 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure from the shower head and 8.0 gpm (30.3 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure from the eye/facewash. Unit shall provide a non-injurious stream of water for 15 minutes or longer as required by ANSI Z358.1. Combination unit shall be supplied with stainless steel single motion activation stay open ball valves. Valve sizes: shower 1", eye/facewash 1/2". Unit shall include S/S actuators with actuation graphics, schedule 40 stainless steel piping and 1 1/4" supply/waste connection with flanged floor mounting plate for free-standing installation. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator. Eye/Facewash heads to be supplied with self-adjusting 8.0 gpm (30.3 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of corrosion resistant long lasting stainless steel. Shower head must deliver a minimum of 20" (50.8cm) diameter pattern to the target area 60" (152.4cm) above standing level. Eye/Facewash heads with float off covers to be manufactured of UV resistant long lasting ABS plastic mounted on a chrome plated brass wye in a type 304 S/S bowl. Float off covers are secured with stainless steel bead chains and provided to inhibit dust and/or contamination when not in use. Combination units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable. Wheelchair accessible combination unit shall be Encon Safety Products Model 0105394SS.

**MATERIALS OF CONSTRUCTION:**

**PIPING:** Schedule 40 stainless steel.

**VALVES:** Stainless steel stay open ball valves with chrome plated balls, stainless steel valve stems, stainless steel push plate with actuation graphic (eye/facewash) and stainless steel pull chains with actuation graphic (shower). Valve sizes: shower 1", eye/facewash 1/2".

**SHOWER HEAD:** Stainless steel shower head delivers a minimum of 20" (50.8cm) diameter pattern to the target area 60" (152.4cm) above standing level.

**EYE/FACEWASH HEAD:** ABS plastic dual stream heads with ABS plastic float off covers secured with stainless steel bead chains and chrome plated brass wye assembly.

