



1-800-283-6266

phone: (713) 466-1449

email: customerservice@enconsafety.com

CASCAIDE® EYEWASH W/SST BOWL AND WALL BRACKET PART NUMBER: CC02210

SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 2.40 gpm (9.08 lpm) @ 30/70 psi (206.84/482.63 kPa) of flowing pressure. Eyewash shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 1/2" bronze chrome plated (BCP) single motion activation stay open ball valve with CP ball. Eyewash shall include SST actuator with actuation graphic, 7" x 11" (17.78 cm x 27.94 cm) sign and SST wall mounting bracket. Unit must be supplied with self-adjusting 2.40 gpm (9.08 L/min) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.84/482.63 kPa) hydraulic conditions. Eyewash heads with integral hinged covers to be manufactured of solvent resistant acetal mounted on chrome plated brass wye in a type 304 stainless steel bowl.

Eyewash covers are provided to inhibit dust and/or contamination when not in use. Eyewash units with deteriorating screens/filters are not acceptable.

The supply for the unit will be installed above the drain, eliminating backflow opportunity.

MATERIALS OF CONSTRUCTION:

PIPING: 1/2" Chrome plated brass.

VALVES: 1/2" Chrome plated bronze stay open ball valve with chrome plated ball, SST valve stem and SST push plate with actuation graphic.

EYEWASH HEAD: Acetal dual stream heads with integral hinged covers and chrome plated brass wye assembly.

BOWL: Type 304 Stainless Steel bowl with SST wall mount bracket.

REGULATOR: Self-adjusting 2.40 gpm (9.08 L/min) regulator assures a constant and even dual stream flow pattern under varying hydraulic conditions.

SUPPLY: 1/2" NPT

WASTE: 1 1/2" NPT

